



GENERAL NOTES:

FOR 2" INSTALLATIONS REPLACE ALL 1" MATERIALS WITH 2"

NOTE:

- | | |
|---|---|
| <p>(N1) 1 EA. C.I. DOUBLE STRAP SADDLE, TAPPED 1" (202S ROMAC)</p> <p>(N2) 1 EA. 1" BRONZE CORP. STOP, MALE I.P. x MALE I.P.</p> <p>(N3) 5 EA. 1" GALVANIZED 90° ELLS & NIPPLES</p> <p>(N4) 1" EA. 1" x VARIABLE LENGTH GALVANIZED PIPE</p> <p>(N5) 1" BALL STOP (FORD)</p> <p>(N6) C.I. VALVE BOX</p> <p>(N7) 1 EA. 1" AIR/VACUUM RELIEF VALVE, w/SCREEN MESH OVER DOUBLE 90° ELL ("APCO" No. 143C OR EQUAL)</p> | <p>(N8) 4' DIA. x 5" WALL PRECAST MANHOLE—FLAT TOP FOR HIGHWAY TRAFFIC, 30" MANHOLE FRAME & COVER WITH CONCRETE LEVELING RINGS IF REQUIRED, 4' DEEP</p> <p>(N9) WASHED CRUSHED ROCK, 100% MAX. 1-1/2", 5% THROUGH 1/4" SCREEN, 6" DEEP</p> <p>(N10) PAVEMENT SURFACE</p> <p>(N11) CURB</p> <p>(N12) GROUT</p> <p>(N13) WATER MAIN</p> |
|---|---|